

DMS Wireless

806-960 MHz 180° V-POL

Electrical Data

Frequency:	806-960 MHz
Gain:	12 dBi
VSWR:	<1.5:1
Polarization:	Vertical
Horizontal Beamwidth :	180°
Vertical Beamwidth:	13°
Nominal Impedance:	50 Ohms
F/B Ratio:	>20 dB
Max Input Power:	250 W
Lightning Protection:	DC Ground


Mechanical Data

Connector :	N Female
Dimensions:	1270*290*130mm
length*width*height	/50.0*11.4*5.1in
Weight:	10.5kg/23.1lb
Reflector Material:	Aluminum Alloy
Radome Material:	UV Resistance PVC
Mounting Method:	Mast
Mast Size:	Ø50-Ø90mm
Rated Wind Velocity:	210km/h
Operating temperature:	-40~+65℃


Shipment Data

Packing Qty:	1 pc/Carton
Carton Size:	1670*330*195mm
(length*width*height)	65.7*13.0*7.7in
Packing Weight:	12.3kg/27.1lb



PA806-960-180-12V



H-Plane



V-Plane



Range: 0~15 deg

Email: sales@dmswireless.com
www.dmswireless.com

Notice: Specifications are subject to change without notice.
 Images may not reflect the actual product.