

806-960/1710-2500 MHz H-POL or V-POL

Electrical Data

Frequency:	806-960/1710-2500 MHz
Gain:	9 dBi
VSWR:	<1.5:1
Polarization:	Horizontal or Vertical
Horizontal Beamwidth :	65°
Vertical Beamwidth:	55°
Nominal Impedance:	50 Ohms
F/B Ratio:	>14 dB
Max Input Power:	100 W
Lightning Protection:	DC Ground


Mechanical Data

Connector :	N Female
Dimensions:	300*210*65mm
(length*width*height)	/11.8*8.3*2.9 in
Weight:	0.8kg/1.8lb
Cable Length:	300mm/11.8in
Reflector Material:	Aluminum Alloy
Radome Material:	Weatherproof ABS
Mounting Method:	Mast
Mast Size:	Ø40-Ø50mm
Rated Wind Velocity:	210km/h
Operating temperature:	-40~+65°C


Shipment Data

Packing Qty:	10pcs/Carton
Carton Size:	460*450*450mm
(length*width*height)	18.1*17.7*17.7in
Packing Weight:	9.5kg/20.9lb

YAR806-2500-9HV



H-Plane



V-Plane

Email: sales@dmswireless.com
www.dmswireless.com

*Notice: Specifications are subject to change without notice.
Images may not reflect the actual product.*